

# Product datasheet

Specifications



APC Easy UPS On-Line, 15kVA/  
15kW, Rackmount 3U, 230V, 1x  
Hard wire 3-wire(1P+N+E) outlet,  
Intelligent Card Slot, No battery,  
W/O rail kit

SRV15KUXI-IN

## Overview

|                     |   |
|---------------------|---|
| <b>Presentation</b> | High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions. |
| <b>Lead time</b>    | Usually in Stock  |

## Main

|   |  |
|---|--|
| <b>Main Input Voltage</b>               | 230 V AC 1 phase<br>400 V AC 3 phases                              |
| <b>Input voltage</b>                    | 220 V<br>230 V<br>415 V  |
| <b>Input voltage limits</b>             | 110...300 V half load<br>176...300 V full load                     |
| <b>Number of input connectors</b>       | 1 hard wire 3-wire (1P + N + E)<br>1 hard wire 5-wire (3P + N + E) |
| <b>Network frequency</b>                | 40...70 Hz auto sensing  |
| <b>Output voltage</b>                   | 230 V AC 1 phase   |
| <b>Output voltage</b>                   | 220 V<br>240 V   |
| <b>Rated power in W</b>                 | 15000 W  |
| <b>rated power in VA</b>                | 15000 VA   |
| <b>Output connector type</b>            | Hard wire 3-wire (1P + N + E) for 1 zone(s)                        |
| <b>Bypass type</b>                      | Internal bypass (automatic and manual)                             |
| <b>Crest factor</b>                     | 3 : 1  |
| <b>Harmonic distortion</b>              | 2 %  |
| <b>Maximum configurable power in VA</b> | 15000 VA   |
| <b>Maximum configurable power in W</b>  | 15000 W  |
| <b>UPS type</b>                         | On-Line  |
| <b>Wave type</b>                        | Sine wave  |
| <b>Efficiency</b>                       | 95 % (full load)   |
| <b>Output frequency</b>                 | 50/60 Hz +/- 3 Hz sync to mains                                    |

## Complementary

|                               |  |
|-------------------------------|--|
| <b>Additional information</b> | Configurable for 220 : 230 or 240 nominal output voltage |
| <b>Battery type</b>           | Lead-acid external sold separately                       |

|                                  |  |
|----------------------------------|--|
| <b>Control panel</b>             | Multifunction LCD status and control console   |
| <b>Emergency power off</b>       | Yes  |
| <b>Alarm</b>                     | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| <b>UPS connectivity</b>          | Serial port<br>USB port<br>Available expansion slot                                    |
| <b>Surge energy rate</b>         | 600 J  |
| <b>Number of rack unit</b>       | 3U   |
| <b>Colour</b>                    | Black (RAL 7010)   |
| <b>Height</b>                    | 130 mm   |
| <b>Width</b>                     | 438 mm   |
| <b>Depth</b>                     | 749 mm   |
| <b>Product weight</b>            | 29 kg  |
| <b>Mounting location</b>         | Front  |
| <b>Mounting preference</b>       | No preference  |
| <b>Mounting mode</b>             | Rack-mounted with kit  |
| <b>USB compatible</b>            | Yes  |
| <b>Mounting position</b>         | Horizontal   |
| <b>Mounting mode</b>             | Rack-mounted with kit sold separately  |
| <b>Redundant</b>                 | No   |
| <b>Range of product</b>          | Easy UPS On-Line   |
| <b>Product or component type</b> | Uninterruptible power supply (UPS)   |

## Environment

|  |                         |
|--|-------------------------|
| <b>Product certifications</b>                | CE                      |
| <b>Ambient air temperature for operation</b> | 0...40 °C               |
| <b>Ambient air temperature for storage</b>   | -20...60 °C             |
| <b>Storage altitude</b>                      | 0...15000 m             |
| <b>IP degree of protection</b>               | IP20                    |
| <b>Relative humidity</b>                     | 0...95 % non-condensing |
| <b>Storage Relative Humidity</b>             | 0...95 % non-condensing |
| <b>Acoustic level</b>                        | 65 dBA                  |
| <b>Heat dissipation</b>                      | 2503 Btu/h              |
| <b>Operating altitude</b>                    | 0...3000 m              |

## Batteries & Runtime

|                                       |                         |
|---------------------------------------|-------------------------|
| <b>Battery type</b>                   | External battery system |
| <b>Battery voltage</b>                | +/- 120 V               |
| <b>Extended runtime</b>               | 0                       |
| <b>Number of battery filled slots</b> | 0                       |
| <b>Number of battery free slots</b>   | 0                       |

---

|                       |              |
|-----------------------|--------------|
| Battery charger power | 2340 W rated |
|-----------------------|--------------|

## Packing Units

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

---

|                              |   |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

---

|                  |       |
|------------------|-------|
| Package 1 Height | 25 cm |
|------------------|-------|

---

|                 |       |
|-----------------|-------|
| Package 1 Width | 87 cm |
|-----------------|-------|

---

|                  |       |
|------------------|-------|
| Package 1 Length | 58 cm |
|------------------|-------|

---

|                  |         |
|------------------|---------|
| Package 1 Weight | 35.9 kg |
|------------------|---------|

## Contractual warranty

---

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|  |   |
|--|---|
| Total lifecycle Carbon footprint                       | 7 095 kg CO2 eq.                              |
| Carbon footprint of the manufacturing phase [A1 to A3] | 283 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 3 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 9 540 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 3 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

### Use Better



### Materials and Substances

|  |   |
|--|---|
| Packaging made with recycled cardboard | No  |
| Packaging without single use plastic   | No  |
| SCIP Number                            | 080b8d64-796e-42e7-a17d-31b86e55d143  |
| EU RoHS Directive                      | <a href="#">Compliant</a>   |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a> |

### Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

### Use Again



### Repack and remanufacture

|                                 |   |
|---------------------------------|---|
| Recyclability potential, in %   | 65                                      |
| End of life manual availability | <a href="#">End of Life Information</a> |
| Take-back                       | No                                      |

Image of product / Alternate images

**Alternative**

---



